



Electrical:

1. Turn ratio: 1~2:J1~J2=1CT:1CT(±2%),
7~8:J3~J6=1CT:1CT(±2%).
2. OCL: 350uH Min. at 100KHz 100mV 8mA DC.
3. Insertion Loss: -1.0 dB Max 1~100MHz.
4. Return loss: -20dB Min 1~10MHz;
-16dB Min 10~30MHz;
-12dB Min 30~60MHz;
-10dB Min 60~80MHz.
5. Cross talk: -40dB Min 1~30MHz;
-35dB Min 30~60MHz;
-30dB Min 60~100MHz;
6. CMR: -30dB Min 1~100MHz;
7. HI-Pot: 1500V AC & 2250V DC
6S 1mA PRI TO SEC

LED SPECIFICATIONS (WITH FORWARD CURRENT OF 20 mA)		
STANDARD LED	WAVELENGTH	FORWARD (A)
GREEN	568nm	20mA
YELLOW	585 nm	20mA

**RJ45 MAGNETIC JACK WITH LED, 8P, 8C
SHIELDED/10/100 Mbps FILTER**

ACAD REFERENCE NO.: A64-112-231N420

DRAWN: R.STA.MONICA DATE: APR.15/2015

CHECKED: R.S.M. DATE: NOV.03/2021

PART NUMBER

SEE NOTE

DRAWING NUMBER

A64-112-231N420

ISSUE

3



THIS SERIES FULLY CONFORMS TO THE
EUROPEAN UNION DIRECTIVES
2011/65/EU FOR ROHS COMPLIANCY.



EDAC INC
TORONTO, ONTARIO
CANADA

YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC. AND
SHALL NOT BE REPRODUCED OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.